



**SAFETY DATA SHEET of:**  
**MonoPrime UNI base**

Revision date: Friday, June 1, 2018

**1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:**

**1.1 Product identifier:**

**MonoPrime UNI base**

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

/

Concentration in use: /

**1.3 Details of the supplier of the safety data sheet:**

**PROKOL**

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 — Fax: 0031492547592

E-mail: [jw.koolen@prokol.nl](mailto:jw.koolen@prokol.nl) — Website: <http://www.prokol.nl/>

**1.4 Emergency telephone number:**

+313 02 74 88 88

**2 SECTION 2: Hazards identification:**

**2.1 Classification of the substance or mixture:**

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

**EUH066 H226 Flam. Liq. 3 H317 Skin Sens. 1 H335 STOT SE 3 H336 STOT SE 3 H373 STOT RE 2  
H411 Aquatic Chronic 2**

**2.2 Label elements:**

Pictograms:



Signal word:

## Warning

### Hazard statements:

<b>EUH066:</b>	Repeated exposure may cause skin dryness or cracking.
<b>H226 Flam. Liq. 3:</b>	Flammable liquid and vapour.
<b>H317 Skin Sens. 1:</b>	May cause an allergic skin reaction.
<b>H335 STOT SE 3:</b>	May cause respiratory irritation.
<b>H336 STOT SE 3:</b>	May cause drowsiness or dizziness.
<b>H373 STOT RE 2:</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H411 Aquatic Chronic 2:</b>	Toxic to aquatic life with long lasting effects.

### Precautionary statements:

<b>P261:</b>	Avoid breathing dust/vapours/spray.
<b>P280:</b>	Wear protective gloves, protective clothing, eye protection, face protection.
<b>P312:</b>	Call a POISON CENTER or doctor if you feel unwell.
<b>P362+P364:</b>	Take off contaminated clothing and wash it before reuse.
<b>P403+P233:</b>	Store in a well-ventilated place. Keep container tightly closed.
<b>P501:</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

### Contains:

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) polyacrylate Hydrocarbons, C9, aromatics

### 2.3 Other hazards:

none

## 3 SECTION 3: Composition/information on ingredients:

polyacrylate	≤ 40 %	CAS number: polymer EINECS: REACH Registration number: CLP Classification: <b>H317 Skin Sens. 1</b>
Hydrocarbons, C9, aromatics	≤ 30 %	CAS number: EINECS: 918-668-5 REACH Registration number: 01-2119455851-35 CLP Classification: <b>EUH066 H226 Flam. Liq. 3 H304 Asp. Tox. 1 H335 STOT SE 3 H336 STOT SE 3 H411 Aquatic Chronic 2</b>
Barium sulphate	≤ 5 %	CAS number: 7727-43-7 EINECS: 231-784-4 REACH Registration number: Annex V CLP Classification:

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	≤ 2 %	CAS number: EINECS: REACH Registration number: CLP Classification:	919-446-0 01-2119458049-33 <b>EUH066</b> <b>H226 Flam. Liq. 3</b> <b>H304 Asp. Tox. 1</b> <b>H336 STOT SE 3</b> <b>H372 STOT RE 1</b> <b>H411 Aquatic Chronic 2</b>
Xylene, mixture of isomers	≤ 0.7 %	CAS number: EINECS: REACH Registration number: CLP Classification:	1330-20-7 215-535-7 01-2119488216-32 <b>H226 Flam. Liq. 3</b> <b>H304 Asp. Tox. 1</b> <b>H312 Acute tox. 4</b> <b>H315 Skin Irrit. 2</b> <b>H319 Eye Irrit. 2</b> <b>H332 Acute tox. 4</b> <b>H335 STOT SE 3</b> <b>H373 STOT RE 2</b>
Ethylbenzene	≤ 0.3 %	CAS number: EINECS: REACH Registration number: CLP Classification:	100-41-4 202-849-4 01-2119489370-35 <b>H225 Flam. Liq. 2</b> <b>H304 Asp. Tox. 1</b> <b>H332 Acute tox. 4</b> <b>H373 STOT RE 2</b> <b>H412 Aquatic Chronic 3</b>

For the full text of the H phrases mentioned in this section, see section 16.

## 4 SECTION 4: First aid measures:

### 4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

<b>Skin contact:</b>	remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.
<b>Eye contact:</b>	first prolonged rinsing with water (contact lenses to be removed if this is easily done) then take to physician.
<b>Ingestion:</b>	rinse mouth, do not induce vomiting, take to hospital immediately.
<b>Inhalation:</b>	let sit upright, fresh air, rest and take to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed:

<b>Skin contact:</b>	caustic, redness, pain, serious burns
<b>Eye contact:</b>	caustic, redness, blurred vision, pain
<b>Ingestion:</b>	caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach
<b>Inhalation:</b>	headache, dizziness, nausea, drowsiness, unconsciousness

### 4.3 Indication of any immediate medical attention and special treatment needed:

none

## 5 SECTION 5: Fire-fighting measures:

### 5.1 Extinguishing media:

CO<sub>2</sub>, foam, powder, sprayed water

### 5.2 Special hazards arising from the substance or mixture:

none

### 5.3 Advice for firefighters:

**Extinguishing agents to be avoided:** none

## 6 SECTION 6: Accidental release measures:

### 6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

### 6.2 Environmental precautions:

do not allow to flow into sewers or open water.

### 6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible remove by using absorbent material.

### 6.4 Reference to other sections:

for further information check sections 8 & 13.

## 7 SECTION 7: Handling and storage:

### 7.1 Precautions for safe handling:

handle with care to avoid spillage.

### 7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

### 7.3 Specific end use(s):

/





## 8 SECTION 8: Exposure controls/personal protection:

### 8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

Hydrocarbons, C<sub>9-12</sub>, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 533 mg/m<sup>3</sup>, 2-methoxy-1-methylethyl acetate 275 mg/m<sup>3</sup>, n-Butylacetate 238 mg/m<sup>3</sup>, Xylene, mixture of isomers 221 mg/m<sup>3</sup>, Ethylbenzene 87 mg/m<sup>3</sup>, Barium sulphate 5 mg/m<sup>3</sup>

## 8.2 Exposure controls:

<b>Inhalation protection:</b>	use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
<b>Skin protection:</b>	handling with butyl-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
<b>Eye protection:</b>	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
<b>Other protection:</b>	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

## 9 SECTION 9: Physical and chemical properties:

### 9.1 Information on basic physical and chemical properties:

<b>Melting point/melting range:</b>	/
<b>Boiling point/Boiling range:</b>	100 °C — 331 °C
<b>pH:</b>	/
<b>pH 1% diluted in water:</b>	/
<b>Vapour pressure/20°C,:</b>	600 Pa
<b>Vapour density:</b>	not applicable
<b>Relative density, 20°C:</b>	1.1182 kg/l
<b>Appearance/20°C:</b>	liquid
<b>Flash point:</b>	40 °C
<b>Flammability (solid, gas):</b>	not applicable
<b>Auto-ignition temperature:</b>	260 °C
<b>Upper flammability or explosive limit, (Vol %):</b>	6.000 %
<b>Lower flammability or explosive limit, (Vol %):</b>	0.700 %
<b>Explosive properties:</b>	not applicable
<b>Oxidising properties:</b>	not applicable
<b>Decomposition temperature:</b>	/
<b>Solubility in water:</b>	not soluble
<b>Partition coefficient: n-octanol/water:</b>	not applicable
<b>Odour:</b>	characteristic
<b>Odour threshold:</b>	not applicable
<b>Dynamic viscosity, 20°C:</b>	600 mPa.s
<b>Kinematic viscosity, 40°C:</b>	537 mm <sup>2</sup> /s
<b>Evaporation rate (n-BuAc = 1):</b>	0.840

### 9.2 Other information:

<b>Volatile organic component (VOC):</b>	29.68 %
<b>Volatile organic component (VOC):</b>	318.389 g/l
<b>Sustained combustion test :</b>	/

## 10 SECTION 10: Stability and reactivity:

### 10.1 Reactivity:

stable under normal conditions.

### 10.2 Chemical stability:

extremely high or low temperatures.

### 10.3 Possibility of hazardous reactions:

none

### 10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

### 10.5 Incompatible materials:

acids, alkalines, oxidants, reductants

### 10.6 Hazardous decomposition products:

doesn't decompose with normal use

## 11 SECTION 11: Toxicological information:

### 11.1 Information on toxicological effects:

<b>H317 Skin Sens. 1:</b>	May cause an allergic skin reaction.
<b>H335 STOT SE 3:</b>	May cause respiratory irritation.
<b>H336 STOT SE 3:</b>	May cause drowsiness or dizziness.
<b>H373 STOT RE 2:</b>	May cause damage to organs through prolonged or repeated exposure.

**Calculated acute toxicity, ATE oral:** /

**Calculated acute toxicity, ATE dermal:** /

polyacrylate	LD50 oral, rat: ≥ 5 000 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
Hydrocarbons, C9, aromatics	LD50 oral, rat: 3 492 mg/kg LD50 dermal, rabbit: 3 160 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
Barium sulphate	LD50 oral, rat: ≥ 5 000 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 oral, rat: 2 000 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l

Xylene, mixture of isomers	LD50 oral, rat: $\geq 5\ 000$ mg/kg LD50 dermal, rabbit: 1 000 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
Ethylbenzene	LD50 oral, rat: 3 500 mg/kg LD50 dermal, rabbit: $\geq 5\ 000$ mg/kg LC50, Inhalation, rat, 4h: 11 mg/l

## 12 SECTION 12: Ecological information:

### 12.1 Toxicity:

Xylene, mixture of isomers	LC50 (Fish): 1-10 mg/L (96h) EC50 (Daphnia): 1-10 mg/L (96h) EC50 (Algae): 1-10 mg/L (96h)
----------------------------	--

### 12.2 Persistence and degradability:

No additional data available

### 12.3 Bioaccumulative potential:

No additional data available

### 12.4 Mobility in soil:

**Water hazard class, WGK (AwSV):** 2

**Solubility in water:** not soluble

### 12.5 Results of PBT and vPvB assessment:

No additional data available

### 12.6 Other adverse effects:

No additional data available

## 13 SECTION 13: Disposal considerations:

### 13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

## 14 SECTION 14: Transport information:

### 14.1 UN number:

1263

### 14.2 UN proper shipping name:

UN 1263 Paint, 3, III, (D/E)

### 14.3 Transport hazard class(es):

**Class(es):** 3  
**Identification number of the hazard:** 30

### 14.4 Packing group:

III

### 14.5 Environmental hazards:

environmentally hazardous

### 14.6 Special precautions for user:

**Hazard characteristics:** Risk of fire. Risk of explosion. Containments may explode when heated.  
**Additional guidance:** Take cover. Keep out of low areas.



## 15 SECTION 15: Regulatory information:

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

**Water hazard class, WGK (AwSV):** 2  
**Volatile organic component (VOC):** 29.677 %  
**Volatile organic component (VOC):** 318.389 g/l  
**Composition by regulation (EC) 648/2004:** Aromatic hydrocarbons 15% - 30%

### 15.2 Chemical Safety Assessment:

No data available

## 16 SECTION 16: Other information:

### Legend to abbreviations used in the safety data sheet:

**ADR:** The European Agreement concerning the International Carriage of Dangerous Goods by Road  
**BCF:** Bioconcentration factor  
**CAS:** Chemical Abstracts Service  
**CLP:** Classification, Labelling and Packaging of chemicals  
**EINECS:** European INventory of Existing Commercial chemical Substances  
**Nr.:** number  
**PTB:** persistent, toxic, bioaccumulative  
**TLV:** Threshold Limit Value  
**vPvB:** very persistent and very bioaccumulative substances  
**WGK:** Water hazard class



<b>WGK 1:</b>	slightly hazardous for water
<b>WGK 2:</b>	hazardous for water
<b>WGK 3:</b>	extremely hazardous for water

#### Legend to the H Phrases used in the safety data sheet:

**EUH066:** Repeated exposure may cause skin dryness or cracking. **H225 Flam. Liq. 2:** Highly flammable liquid and vapour. **H226 Flam. Liq. 3:** Flammable liquid and vapour. **H304 Asp. Tox. 1:** May be fatal if swallowed and enters airways. **H312 Acute tox. 4:** Harmful in contact with skin. **H315 Skin Irrit. 2:** Causes skin irritation. **H317 Skin Sens. 1:** May cause an allergic skin reaction. **H319 Eye Irrit. 2:** Causes serious eye irritation. **H332 Acute tox. 4:** Harmful if inhaled. **H335 STOT SE 3:** May cause respiratory irritation. **H336 STOT SE 3:** May cause drowsiness or dizziness. **H372 STOT RE 1:** Causes damage to organs through prolonged or repeated exposure. **H373 STOT RE 2:** May cause damage to organs through prolonged or repeated exposure. **H411 Aquatic Chronic 2:** Toxic to aquatic life with long lasting effects. **H412 Aquatic Chronic 3:** Harmful to aquatic life with long lasting effects.

#### CLP Calculation method:

Calculation method

#### Reason of revision, changes of following items:

Sections: 9.1, 9.2

#### MSDS reference number:

ECM-105817,00

*This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.*