PROKOL

SAFETY DATA SHEET of:

Rocathaan Filler GF-400, base

Revision date: Thursday, September 2, 2021

S102.300

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Rocathaan Filler GF-400, base

1.2	Relevant identified uses of the substance or mixture and uses advised against:
/	
Con	centration in use: /

1.3 Details of the supplier of the safety data sheet:

PROKOL

UFI:

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 — E-mail: jw.koolen@prokol.nl — Website: http://www.prokol.nl/

1.4 Emergency telephone number:

+313 02 74 88 88

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

EUH208 H315 Skin Irrit. 2 H319 Eye Irrit. 2 H411 Aquatic Chronic 2

2.2 Label elements:

Pictograms:



Signal word:

Warning

Hazard statements:

EUH208: Contains (N-Formylmorpholin; 3-aminopropyltriethoxysilane). May produce an

allergic reaction.

H315 Skin Irrit. 2: Causes skin irritation.

H319 Eye Irrit. 2: Causes serious eye irritation.

H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Precautionary statements:

P264: Wash hands thoroughly after handling.
P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international

regulations.

Contains:

N-Formylmorpholin 3-aminopropyltriethoxysilane

2.3 Other hazards:

None

3 SECTION 3: Composition/information on ingredients:

Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	≤ 20 %	CAS number: EINECS: REACH Registration number: CLP Classification:	904-153-2 01-2119488034-38 H319 Eye Irrit. 2
2,4-diamino-3,5-diethyltoluene	≤ 5 %	CAS number: EINECS: REACH Registration number: CLP Classification:	68479-98-1 270-877-4 01-2119486805-25 H302 Acute tox. 4 H312 Acute tox. 4 H319 Eye Irrit. 2 H373 STOT RE 2 H400 Aquatic Acute 1 H410 Aquatic Chronic 1
1,1',1",1"'-ethylenedinitrilotetrapropan-2-ol	≤ 3 %	CAS number: EINECS: REACH Registration number: CLP Classification:	102-60-3 203-041-4 01-2119552434-41 H319 Eye Irrit. 2
3-aminopropyltriethoxysilane	≤ 0.9 %	CAS number: EINECS: REACH Registration number: CLP Classification:	919-30-2 213-048-4 01-2119480479-24 H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1B

Diazabicyclo(5.4.0)undec-7-en e phenol salt, 1,8-, (1:1)	≤ 0.7 %	CAS number: EINECS: REACH Registration number: CLP Classification:	57671-19-9 611-564-8 H302 Acute tox. 4 H314 Skin Corr. 1B
N-Formylmorpholin	≤ 0.5 %	CAS number: EINECS: REACH Registration number: CLP Classification:	4394-85-8 224-518-3 01-2119987993-12 H317 Skin Sens. 1B
Hydrocarbons, C9, aromatics	≤ 0.2 %	CAS number: EINECS: REACH Registration number: CLP Classification:	918-668-5 01-2119455851-35 EUH066 H226 Flam. Liq. 3 H304 Asp. Tox. 1 H335 STOT SE 3 H336 STOT SE 3 H411 Aquatic Chronic 2
Naphta heavy (high boiling point hydrogen treated)	≤ 0.2 %	CAS number: EINECS: REACH Registration number: CLP Classification:	64742-82-1 265-185-4 01-2119490979-12 EUH066 H226 Flam. Liq. 3 H304 Asp. Tox. 1 H336 STOT SE 3 H411 Aquatic Chronic 2

For the full text of the H phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: Remove contaminated clothing, rinse skin with plenty of water, if necessary seek

medical attention.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done) then

take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: None
Eye contact: Redness

Ingestion: Diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: None

4.3 Indication of any immediate medical attention and special treatment needed:

None

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided:

None

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

/

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

8.2 Exposure controls:

Inhalation protection:

Respiratory protection is not required. Use ABEK type gas masks in case of irritating exposure. If necessary, use with sufficient exhaust ventilation.

Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.			
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.			
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.			

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range: /

Boiling point/Boiling range: 100 °C — 400 °C

pH:
pH 1% diluted in water:
Vapour pressure/20°C;

Vapour density:

Relative density, 20°C:

Appearance/20°C:

Flash point:

Not applicable

1.0240 kg/l

Liquid

/

Flammability (solid, gas): Not applicable

Auto-ignition temperature: /
Upper flammability or explosive /

limit, (Vol %):

Lower flammability or explosive

limit, (Vol %):

Explosive properties:

Not applicable

Oxidising properties: Not applicable

Decomposition temperature: /

Solubility in water: Not soluble

Partition coefficient: n- Not applicable

octanol/water:

Odour: characteristic
Odour threshold: Not applicable

Dynamic viscosity, 20°C: 1 mPa.s Kinematic viscosity, 40°C: 1 mm²/s Evaporation rate (n-BuAc = 1): 0.300

9.2 Other information:

Volatile organic component (VOC): 0.24 % Volatile organic component (VOC): 1.290 g/l

Sustained combustion test: /

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H315 Skin Irrit. 2: Causes skin irritation.

H319 Eye Irrit. 2: Causes serious eye irritation.

Calculated acute toxicity, ATE oral: /
Calculated acute toxicity, ATE /

dermal:

Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
2,4-diamino-3,5-diethyltoluene	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	738 mg/kg 1 100 mg/kg ≥ 50 mg/l
1,1',1",1"'-ethylenedinitrilotetrapropan-2-ol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg 10 mg/l
3-aminopropyltriethoxysilane	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	500 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Diazabicyclo(5.4.0)undec-7-en e phenol salt, 1,8-, (1:1)	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	1 160 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
N-Formylmorpholin	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Hydrocarbons, C9, aromatics	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	3 492 mg/kg 3 160 mg/kg ≥ 50 mg/l

Naphta heavy (high boiling point hydrogen treated)	LD50 oral, rat:	≥ 5 000 mg/kg
	LD50 dermal, rabbit:	≥ 5 000 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	LC50 (Fish): NOEC (Fish):	1250 mg/L 500 mg/L
2,4-diamino-3,5-diethyltoluene	LC50 (Fish): EC50 (Daphnia): EC50 (soil microorganism	200 mg/L (48h) 0,5 mg/L (48h) ns): > 170 mg/L (24h)
N-Formylmorpholin	LC50 (Fish):	> 500 mg/l 96h

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1

Solubility in water: Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

3082

14.2 UN proper shipping name:

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (mixture with 2,4-diamino-3,5-diethyltoluene), 9, III, (E)

14.3 Transport hazard class(es):

Class(es): 9

Identification number of the

hazard:

90

14.4 Packing group:

Ш


14.5 Environmental hazards:

Environmentally hazardous

14.6 Special precautions for user:

Hazard characteristics: Risk to the aquatic environment and the sewerage system.

Additional guidance:



15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1

Volatile organic component (VOC): 0.239 % Volatile organic component (VOC): 1.290 g/l

Composition by regulation (EC) Zeolites 5% - 15%

648/2004:

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative

TLV: Threshold Limit Value
UFI: Unique Formula Identifier

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains (N-Formylmorpholin; 3-aminopropyltriethoxysilane). May produce an allergic reaction. H226 Flam. Liq. 3: Flammable liquid and vapour. H302 Acute tox. 4: Harmful if swallowed. H304 Asp. Tox. 1: May be fatal if swallowed and enters airways. H312 Acute tox. 4: Harmful in contact with skin. H314 Skin Corr. 1B: Causes severe skin burns and eye damage. H315 Skin Irrit. 2: Causes skin irritation. H317 Skin Sens. 1B: May cause an allergic skin reaction. H319 Eye Irrit. 2: Causes serious eye irritation. H335 STOT SE 3: May cause respiratory irritation. H336 STOT SE 3: May cause damage to organs through prolonged or repeated exposure. H400 Aquatic Acute 1: Very toxic to aquatic life. H410 Aquatic Chronic 1: Very toxic to aquatic life with long lasting effects.

CLP Calculation method:

Calculation method

Reason of revision, changes of following items:

Sections: 2.1, 2.2, 3, 4.1, 4.2, 9.1, 9.2, 14, 14.2, 14.4, 14.5, 15.1, 16

SDS reference number:

ECM-112408,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.