



# SAFETY DATA SHEET of: Rocapox EP Resin 100 hardener

Revision date: Tuesday, May 5, 2020

## 1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

### 1.1 Product identifier:

Rocapox EP Resin 100 hardener

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

/

Concentration in use: /

### 1.3 Details of the supplier of the safety data sheet:

**PROKOL**

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 — Fax: 0031492547592

E-mail: [jw.koolen@prokol.nl](mailto:jw.koolen@prokol.nl) — Website: <http://www.prokol.nl/>

### 1.4 Emergency telephone number:

+31302748888

## 2 SECTION 2: Hazards identification:

### 2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

**H314 Skin Corr. 1B H317 Skin Sens. 1 H332 Acute tox. 4 H361d Repr. 2 H412 Aquatic Chronic 3**

### 2.2 Label elements:

Pictograms:



Signal word:

Danger

Hazard statements:

<b>H314 Skin Corr. 1B:</b>	Causes severe skin burns and eye damage.
<b>H317 Skin Sens. 1:</b>	May cause an allergic skin reaction.
<b>H332 Acute tox. 4:</b>	Harmful if inhaled.
<b>H361d Repr. 2:</b>	Suspected of damaging the unborn child.
<b>H412 Aquatic Chronic 3:</b>	Harmful to aquatic life with long lasting effects.

Precautionary statements:

<b>P261:</b>	Avoid breathing dust/vapours/spray.
<b>P280:</b>	Wear protective gloves, protective clothing, eye protection, face protection.
<b>P304+P340:</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P308+P313:</b>	IF exposed or concerned: Get medical advice/attention.
<b>P333+P313:</b>	If skin irritation or rash occurs: Get medical advice/attention.
<b>P362+P364:</b>	Take off contaminated clothing and wash it before reuse.

Contains:

m-phenylenebis(methylamine) Benzyl alcohol Phenol, 4,4'-(1- methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethan amine and (chloromethyl)oxirane

2.3 Other hazards:

None

3 SECTION 3: Composition/information on ingredients:

Phenol, 4,4'-(1- methylethylidene)bis-, polymer with 5-amino-1,3,3- trimethylcyclohexanemethan amine and (chloromethyl)oxirane	≤ 50 %	CAS number: 38294-64-3 EINECS: 500-101-4 REACH Registration number: 01-2119965165-33 CLP Classification: <b>H314 Skin Corr. 1B</b> <b>H317 Skin Sens. 1</b> <b>H412 Aquatic Chronic 3</b>
Benzyl alcohol	≤ 40 %	CAS number: 100-51-6 EINECS: 202-859-9 REACH Registration number: 01-2119492630-38 CLP Classification: <b>H302 Acute tox. 4</b> <b>H319 Eye Irrit. 2</b> <b>H332 Acute tox. 4</b>
m-phenylenebis(methylamine)	≤ 10 %	CAS number: 1477-55-0 EINECS: 216-032-5 REACH Registration number: 01-2119480150-50 CLP Classification: <b>H302 Acute tox. 4</b> <b>H314 Skin Corr. 1B</b> <b>H317 Skin Sens. 1</b> <b>H332 Acute tox. 4</b> <b>H412 Aquatic Chronic 3</b>

salicylic acid	≤ 6 %	CAS number:	69-72-7
		EINECS:	200-712-3
		REACH Registration number:	01-2119486984-17
		CLP Classification:	<b>H302 Acute tox. 4</b> <b>H318 Eye Dam. 1</b> <b>H361d Repr. 2</b>

For the full text of the H phrases mentioned in this section, see section 16.

## 4 SECTION 4: First aid measures:

### 4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

<b>Skin contact:</b>	Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.
<b>Eye contact:</b>	Thoroughly rinse with water (contact lenses to be removed if this is easily done) then take to physician.
<b>Ingestion:</b>	Rinse mouth, do not induce vomiting, take to hospital immediately.
<b>Inhalation:</b>	Let sit upright, fresh air, rest and take to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed:

<b>Skin contact:</b>	Caustic, redness, pain, serious burns
<b>Eye contact:</b>	Caustic, redness, blurred vision, pain
<b>Ingestion:</b>	Caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach
<b>Inhalation:</b>	Headache, dizziness, nausea, drowsiness, unconsciousness

### 4.3 Indication of any immediate medical attention and special treatment needed:

None

## 5 SECTION 5: Fire-fighting measures:

### 5.1 Extinguishing media:

CO2, foam, powder, sprayed water

### 5.2 Special hazards arising from the substance or mixture:

None

### 5.3 Advice for firefighters:

**Extinguishing agents to be avoided:** None

## 6 SECTION 6: Accidental release measures:

### 6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

## 6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

## 6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

## 6.4 Reference to other sections:

For further information, check sections 8 & 13.

# 7 SECTION 7: Handling and storage:

## 7.1 Precautions for safe handling:

Handle with care to avoid spillage.

## 7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

## 7.3 Specific end use(s):

/





# 8 SECTION 8: Exposure controls/personal protection:

## 8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

/

## 8.2 Exposure controls:

<b>Inhalation protection:</b>	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
<b>Skin protection:</b>	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
<b>Eye protection:</b>	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
<b>Other protection:</b>	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

# 9 SECTION 9: Physical and chemical properties:

## 9.1 Information on basic physical and chemical properties:

Melting point/melting range: /

<b>Boiling point/Boiling range:</b>	205 °C — 272 °C
<b>pH:</b>	11.0
<b>pH 1% diluted in water:</b>	/
<b>Vapour pressure/20°C,:</b>	/
<b>Vapour density:</b>	Not applicable
<b>Relative density, 20°C:</b>	1.0526 kg/l
<b>Appearance/20°C:</b>	Liquid
<b>Flash point:</b>	110 °C
<b>Flammability (solid, gas):</b>	Not applicable
<b>Auto-ignition temperature:</b>	/
<b>Upper flammability or explosive limit, (Vol %):</b>	/
<b>Lower flammability or explosive limit, (Vol %):</b>	/
<b>Explosive properties:</b>	Not applicable
<b>Oxidising properties:</b>	Not applicable
<b>Decomposition temperature:</b>	/
<b>Solubility in water:</b>	Not soluble
<b>Partition coefficient: n-octanol/water:</b>	Not applicable
<b>Odour:</b>	characteristic
<b>Odour threshold:</b>	Not applicable
<b>Dynamic viscosity, 20°C:</b>	470 mPa.s
<b>Kinematic viscosity, 40°C:</b>	447 mm <sup>2</sup> /s
<b>Evaporation rate (n-BuAc = 1):</b>	0.010

## 9.2 Other information:

<b>Volatile organic component (VOC):</b>	34.00 %
<b>Volatile organic component (VOC):</b>	421.040 g/l
<b>Sustained combustion test :</b>	/

## 10 SECTION 10: Stability and reactivity:

### 10.1 Reactivity:

Stable under normal conditions.

### 10.2 Chemical stability:

Extremely high or low temperatures.

### 10.3 Possibility of hazardous reactions:

None

### 10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

### 10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

### 10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

## 11 SECTION 11: Toxicological information:

### 11.1 Information on toxicological effects:

<b>H314 Skin Corr. 1B:</b>	Causes severe skin burns and eye damage.
<b>H317 Skin Sens. 1:</b>	May cause an allergic skin reaction.
<b>H332 Acute tox. 4:</b>	Harmful if inhaled.
<b>H361d Repr. 2:</b>	Suspected of damaging the unborn child.

**Calculated acute toxicity, ATE oral:** /

**Calculated acute toxicity, ATE dermal:** /

Phenol, 4,4'-(1- methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethan amine and (chloromethyl)oxirane	LD50 oral, rat: ≥ 5 000 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
Benzyl alcohol	LD50 oral, rat: 1 620 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
m-phenylenebis(methylamine)	LD50 oral, rat: 1 180 mg/kg LD50 dermal, rabbit: 3 100 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
salicylic acid	LD50 oral, rat: 891 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l

## 12 SECTION 12: Ecological information:

### 12.1 Toxicity:

Benzyl alcohol	LC50 (Fish): 460 mg/L (72h) EC50 (Daphnia): 230 mg/L (48h) NOEC (Daphnia): 310 mg/L (72h) EC50 (Algae): 770 mg/L (72h)
m-phenylenebis(methylamine)	LC50 (Fish): 87.6 mg/L (96h) EC50 (Daphnia): 87.6 mg/L (96h) EC50 (Algae): 20.3 mg/L (72h) EC50 (soil microorganisms): > 1000 mg/L (30min)
salicylic acid	EC50 (Daphnia): 870 mg/L (48h) EC50 (Algae): > 100 mg/L (72h)

### 12.2 Persistence and degradability:

No additional data available

### 12.3 Bioaccumulative potential:

No additional data available

#### 12.4 Mobility in soil:

**Water hazard class, WGK (AwSV):** 2  
**Solubility in water:** Not soluble

#### 12.5 Results of PBT and vPvB assessment:

No additional data available

#### 12.6 Other adverse effects:

No additional data available

### 13 SECTION 13: Disposal considerations:

#### 13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

### 14 SECTION 14: Transport information:

#### 14.1 UN number:

2735

#### 14.2 UN proper shipping name:

UN 2735 Amines, liquid, corrosive, n.o.s. (mixture with Isophoronediamine; m-phenylenebis(methylamine)) , 8, III, (E)

#### 14.3 Transport hazard class(es):

**Class(es):** 8  
**Identification number of the hazard:** 80

#### 14.4 Packing group:

III

#### 14.5 Environmental hazards:

Not dangerous to the environment

#### 14.6 Special precautions for user:

**Hazard characteristics:** Risk of burns. Risk to the aquatic environment and the sewerage system.  
**Additional guidance:**



## 15 SECTION 15: Regulatory information:

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

<b>Water hazard class, WGK (AwSV):</b>	2
<b>Volatile organic component (VOC):</b>	34.000 %
<b>Volatile organic component (VOC):</b>	421.040 g/l
<b>Composition by regulation (EC) 648/2004:</b>	Preservatives (Salicylic Acid)

### 15.2 Chemical Safety Assessment:

No data available

## 16 SECTION 16: Other information:

### Legend to abbreviations used in the safety data sheet:

<b>ADR:</b>	The European Agreement concerning the International Carriage of Dangerous Goods by Road
<b>ATE:</b>	Acute Toxicity Estimate
<b>BCF:</b>	Bioconcentration factor
<b>CAS:</b>	Chemical Abstracts Service
<b>CLP:</b>	Classification, Labelling and Packaging of chemicals
<b>EINECS:</b>	European INventory of Existing commercial Chemical Substances
<b>LC50:</b>	median Lethal Concentration for 50% of subjects
<b>LD50:</b>	median Lethal Dose for 50% of subjects
<b>Nr.:</b>	Number
<b>PTB:</b>	Persistent, Toxic, Bioaccumulative
<b>TLV:</b>	Threshold Limit Value
<b>vPvB:</b>	very Persistent and very Bioaccumulative substances
<b>WGK:</b>	Water hazard class
<b>WGK 1:</b>	Slightly hazardous for water
<b>WGK 2:</b>	Hazardous for water
<b>WGK 3:</b>	Extremely hazardous for water

### Legend to the H Phrases used in the safety data sheet:

**H302 Acute tox. 4:** Harmful if swallowed. **H314 Skin Corr. 1B:** Causes severe skin burns and eye damage.  
**H317 Skin Sens. 1:** May cause an allergic skin reaction. **H318 Eye Dam. 1:** Causes serious eye damage.  
**H319 Eye Irrit. 2:** Causes serious eye irritation. **H332 Acute tox. 4:** Harmful if inhaled.  
**H361d Repr. 2:** Suspected of damaging the unborn child. **H412 Aquatic Chronic 3:** Harmful to aquatic life with long lasting effects.

### CLP Calculation method:

Calculation method

### Reason of revision, changes of following items:

Sections: 2.1, 2.2, 3, 9.2, 11, 12.4, 15, 15.1, 16

### SDS reference number:

ECM-105766,60



*This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.*