



14041-B - Rocapox Resin 100-TX - Base**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** 14041-B - Rocapox Resin 100-TX - Base
Other means of identification:
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Base for Resin. For professional users only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Prokol Protective Coatings
Duizeldonksestraat 44
5705 CA Helmond - Noord-Brabant - Nederland
Phone: +31 (0) 85 78 200 20
sds@prokol.nl
www.prokol.com
- 1.4 Emergency telephone number:** +31 (0) 85 78 200 20 Mon - Fri 8am - 4.45pm

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
GB CLP Regulation:
Classification of this product has been carried out in accordance with GB CLP Regulation.
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
- 2.2 Label elements:**
GB CLP Regulation:
Warning
-  
- Hazard statements:**
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Precautionary statements:**
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after use.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391: Collect spillage.
P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.
- Supplementary information:**
EUH205: Contains epoxy constituents. May produce an allergic reaction.
- Substances that contribute to the classification**
Bis-[4-(2,3-epoxipropoxy)phenyl]propane; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
- 2.3 Other hazards:**
Product does not meet PBT/vPvB criteria

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and epoxy polymers

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1675-54-3	Bis-[4-(2,3-epoxypropoxy)phenyl]propane Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	50 - <75 %
CAS: 9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	10 - <25 %
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	10 - <25 %
CAS: 25640-78-2	(1-methylethyl)-1,1'-biphenyl Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Eye Irrit. 2: H319 - Danger	5 - <10 %
CAS: 128601-23-0	Hydrocarbons, C9, aromatics Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	2.5 - <5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Bis-[4-(2,3-epoxypropoxy)phenyl]propane CAS: 1675-54-3	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 7: HANDLING AND STORAGE (continued)

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.-Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.-Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.-Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 30 °C
- Maximum time: 12 Months

B.-General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3 EC: 216-823-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4.93 mg/m ³	Non-applicable
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 701-263-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	104.15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	29.39 mg/m ³	Non-applicable
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS: 68609-97-2 EC: 271-846-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3.6 mg/m ³	Non-applicable
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	7.05 mg/m ³	Non-applicable
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3 EC: 216-823-5	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.0893 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.87 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 701-263-0	Oral	Non-applicable	Non-applicable	6.25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62.5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8.7 mg/m ³	Non-applicable
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS: 68609-97-2 EC: 271-846-8	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.87 mg/m ³	Non-applicable
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m ³	Non-applicable

PNEC:


Identification				
Bis-[4-(2,3-epoxypropoxy)phenyl]propane CAS: 1675-54-3 EC: 216-823-5	STP	10 mg/L	Fresh water	0.006 mg/L
	Soil	0.065 mg/kg	Marine water	0.001 mg/L
	Intermittent	0.018 mg/L	Sediment (Fresh water)	0.341 mg/kg
	Oral	0.011 g/kg	Sediment (Marine water)	0.034 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 701-263-0	STP	10 mg/L	Fresh water	0.003 mg/L
	Soil	0.237 mg/kg	Marine water	0 mg/L
	Intermittent	0.025 mg/L	Sediment (Fresh water)	0.294 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.029 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS: 68609-97-2 EC: 271-846-8	STP	10 mg/L	Fresh water	0.106 mg/L
	Soil	1.234 mg/kg	Marine water	0.011 mg/L
	Intermittent	0.072 mg/L	Sediment (Fresh water)	307.16 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	30.72 mg/kg
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8	STP	2 mg/L	Fresh water	0.00054 mg/L
	Soil	0.2699 mg/kg	Marine water	0.000054 mg/L
	Intermittent	0.003 mg/L	Sediment (Fresh water)	1.355 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.1355 mg/kg

8.2 Exposure controls:


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: PVC, Breakthrough time: > 480 min)	Replace the gloves at any sign of deterioration.


As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



D.-Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply):	2.97 % weight
V.O.C. density at 20 °C:	32.67 kg/m ³ (32.67 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Transparent
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	173 - 293 °C
Vapour pressure at 20 °C:	104 Pa
Vapour pressure at 50 °C:	639.52 Pa (0.64 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1100 kg/m ³
Relative density at 20 °C:	1.1

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	221 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Bis-[4-(2,3-epoxypropoxy)phenyl]propane (3); Hydrocarbons, C9, aromatics (3); Bis(2-ethylhexyl) adipate (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS: 68609-97-2	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	LD50 oral	4650 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Hydrocarbons, C9, aromatics CAS: 128601-23-0	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	LC50	2 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	1.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	9.4 mg/L (72 h)	Scenedesmus subspicatus	Algae
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5	LC50	2.54 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	5.55 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1.8 mg/L (72 h)	Selenastrum capricornutum	Algae
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	LC50	0.6 mg/L (96 h)	Oryzias latipes	Fish
	EC50	0.24 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	>100 mg/L (72 h)	Desmodesmus subspicatus	Algae
Hydrocarbons, C9, aromatics CAS: 128601-23-0	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	NOEC	Non-applicable		
	NOEC	0.3 mg/L	Daphnia magna	Crustacean
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	NOEC	Non-applicable		
	NOEC	0.028 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	5 %

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5	BOD5	Non-applicable	Concentration	3 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	BOD5	Non-applicable	Concentration	19.65 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	60 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	Parameter	Value
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	BCF	31
	Pow Log	3
	Potential	Moderate
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5	BCF	150
	Pow Log	3.6
	Potential	High
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	BCF	2896
	Pow Log	5.33
	Potential	Very High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
Bis-[4-(2,3-epoxipropoxy)phenyl]propane CAS: 1675-54-3	Koc	450	Henry	Non-applicable
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5	Koc	4460	Henry	Non-applicable
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
(1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2	Koc	25055	Henry	173.3 Pa·m ³ /mol
	Conclusion	Immobile	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)
- 14.3 Transport hazard class (es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
 - Tunnel restriction code: -
 - Physico-Chemical properties: see section 9
 - Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)
- 14.3 Transport hazard class (es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
 - Special regulations: 335, 969, 274
 - EmS Codes: F-A, S-F
 - Physico-Chemical properties: see section 9
 - Limited quantities: 5 L
 - Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-epoxipropoxi)phenyl]propane)
- 14.3 Transport hazard class (es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
 - Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

- The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.
- The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.
- Control of Substances Hazardous to Health Regulations 2002 (as amended)
- EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H411: Toxic to aquatic life with long lasting effects.
- H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- STOT SE 3: H335 - May cause respiratory irritation.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

- Skin Irrit. 2: Calculation method
- Skin Sens. 1: Calculation method
- Aquatic Chronic 2: Calculation method
- Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- <http://echa.europa.eu>
- <http://eur-lex.europa.eu>

- CONTINUED ON NEXT PAGE -

14041-B - Rocapox Resin 100-TX - Base

SECTION 16: OTHER INFORMATION (continued)

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -