

SAFETY DATA SHEET of: ProFast Multi TR Base

Revision date: Tuesday, August 14, 2018

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

ProFast Multi TR Base

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

PROKOL

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 — Fax: 0031492547592

E-mail: jw.koolen@prokol.nl — Website: http://www.prokol.nl/

1.4 Emergency telephone number:

+31302748888

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H317 Skin Sens. 1 H319 Eye Irrit. 2 H412 Aquatic Chronic 3

2.2 Label elements:

Pictograms:



Signal word:

Warning

Hazard statements:

H317 Skin Sens. 1: May cause an allergic skin reaction.H319 Eye Irrit. 2: Causes serious eye irritation.

H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Precautionary statements:

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

Contains:

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane tetraethyl N,N'-(methylene di cyclohexane-4,1-diyl)bis-DL-aspartate

2.3 Other hazards:

none

3 SECTION 3: Composition/information on ingredients:

tetraethyl N,N'-(methylene di cyclohexane-4,1-diyl)bis-DL-aspartate	> 30%	CAS number: EINECS: REACH Registration number: CLP Classification:	136210-30-5 429-270-1 01-0000017556-64 H317 Skin Sens. 1 H412 Aquatic Chronic 3
bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	> 30%	CAS number: EINECS: REACH Registration number: CLP Classification:	136210-32-7 412-060-9 01-0000015937-58 H317 Skin Sens. 1 H412 Aquatic Chronic 3
diethyl fumarate	< 5%	CAS number: EINECS: REACH Registration number: CLP Classification:	623-91-6 210-819-7 H302 Acute tox. 4 H315 Skin Irrit. 2 H318 Eye Dam. 1 H335 STOT SE 3

For the full text of the H & R phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: remove contaminated clothing, rinse with plenty of water, if necessary seek medical

attention.

Eye contact: first prolonged rinsing with water (contact lenses to be removed if this is easily done)

then take to physician.

Ingestion: rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: redness, pain

Eye contact: redness, pain, bad looking

Ingestion: diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: sore throat, cough, shortness of breath, headache

4.3 Indication of any immediate medical attention and special treatment needed:

none

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

none

5.3 Advice for firefighters:

Extinguishing agents to be

avoided:

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

none

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up windRemove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible remove by using absorbent material.

6.4 Reference to other sections:

for further information check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

8.2 Exposure controls:

Inhalation protection:	if necessary, use an air-purifying face mask in case of respiratory hazards.	
Skin protection:	handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:

Boiling point/Boiling range: 100 °C — 100 °C

pH: pH 1% diluted in water: Vapour pressure/20°C,:

Vapour density: not applicable Relative density, 20°C: 1.0600 kg/l Appearance/20°C: liquid Flash point: 74 °C

Flammability (solid, gas): not applicable

Auto-ignition temperature: Upper flammability or explosive

limit, (Vol %):

limit, (Vol %):

Lower flammability or explosive

Explosive properties: not applicable Oxidising properties: not applicable

Decomposition temperature:

Solubility in water: not soluble

Partition coefficient: n- not applicable

octanol/water:

Odour: characteristic
Odour threshold: not applicable
Dynamic viscosity, 20°C: 1 380 mPa.s
Kinematic viscosity, 40°C: 1 302 mm²/s

Evaporation rate (n-BuAc = 1): 0.300

9.2 Other information:

Volatile organic component (VOC):

Volatile organic component (VOC): 0.000 g/l

Sustained combustion test: /

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

stable under normal conditions.

10.2 Chemical stability:

extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

none

10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

doesn't decompose with normal use

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H317 Skin Sens. 1: May cause an allergic skin reaction.

H319 Eye Irrit. 2: Causes serious eye irritation.

Calculated acute toxicity, ATE oral: //
Calculated acute toxicity, ATE

dermal:

tetraethyl N,N'-(methylene di cyclohexane-4,1-diyl)bis-DL-aspartate	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l
bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l
diethyl fumarate	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

tetraethyl N,N'-(methylene di cyclohexane-4,1-diyl)bis-DL-aspartate	LC50 (Fish): EC50 (Daphnia): NOEC (Daphnia): EC50 (Algae): EC50 (soil microorganisms):	66 mg/L (Danio rerio)(96h) 88,6 mg/L (48 h) 0,01 mg/L (21 d) IC50 113 mg/L 3,110 mg/L (3h)
bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	LC50 (Fish): EC50 (Daphnia): NOEC (Daphnia): NOEC (Algae): EC50 (soil microorganisms):	66 mg/L (Danio rerio)(96h) 88,6 mg/L (48 h) 0,01 mg/L (21 d) 3,110 mg/L (3h) IC50: 113 mg/L

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

	Additional data:
tetraethyl N,N'-(methylene di cyclohexane-4,1-diyl)bis-DL-aspartate	Log Pow: 5,16 (20°C)

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1

Solubility in water: not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

not applicable

14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

14.3 Transport hazard class(es):

Class(es): not applicable ldentification number of the hazard:

14.4 Packing group:

not applicable

14.5 Environmental hazards:

not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: not applicable
Additional guidance: not applicable

15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1
Volatile organic component (VOC): /

Volatile organic component (VOC): 0.000 g/l Composition by regulation (EC) none

648/2004:

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing Commercial chemical Substances

Nr.: number

PTB: persistent, toxic, bioaccumulative

TLV: Threshold Limit Value

vPvB: very persistent and very bioaccumulative substances

WGK: Water hazard class

WGK 1: slightly hazardous for water

WGK 2: hazardous for water

WGK 3: extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

H302 Acute tox. 4: Harmful if swallowed.
 H315 Skin Irrit. 2: Causes skin irritation.
 H317 Skin Sens. 1: May cause an allergic skin reaction.
 H318 Eye Dam. 1: Causes serious eye damage.
 H319 Eye Irrit. 2: Causes serious eye irritation.
 H310 Eye Irrit. 2: Causes serious eye irritation.
 H311 Eye Irrit. 2: Causes exerious eye irritation.
 H311 Eye Irrit. 2: Causes exerious eye irritation.
 H312 Eye Irrit. 2: Causes exerious eye irritation.
 H312 Eye Irrit. 2: Causes exerious eye irritation.
 H313 Eye Irrit. 2: Causes exerious eye irritation.
 H314 Eye Irrit. 2: Causes exerious eye irritation.
 H315 Eye Irrit. 2: Causes

Reason of revision, changes of following items:

Sections: 2.1, 2.2, 16

MSDS reference number:

ECM-105803,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.