

SAFETY DATA SHEET of:

Rocapox EP Floorcoating WD-600 Hardener

Revision date: Thursday, May 7, 2015

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Rocapox EP Floorcoating WD-600 Hardener

1.2 Relevant identified uses of the substance or mixture and uses advised against:

/

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

PROKOL

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 — Fax: 0031492547592

E-mail: jw.koolen@prokol.nl — Website: http://www.prokol.nl/

1.4 Emergency telephone number:

0031302748888

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H411 Aquatic Chronic 2

Classification of the substance or mixture in accordance with regulation 67/548/EC:

R36/38: Irritant R43: Irritant R51/53: Dangerous to the environment

2.2 Label elements:

Symbols:



Signal word:

Warning

Hazard statements:

H315 Skin Irrit. 2: Causes skin irritation.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H319 Eye Irrit. 2: Causes serious eye irritation.

H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Precautionary statements:

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

Contains:

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight ≤ 700)

2.3 Other hazards:

none

3 SECTION 3: Composition/information on ingredients:

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	15% - 30%	CAS number:	3101-60-8
		EINECS:	221-453-2
		REACH Registration number:	
		CLP Classification:	H315 Skin Irrit. 2 H317 Skin Sens. 1 H411 Aquatic Chronic 2
		R-Phrases:	R36/38 R43 R51/53
Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight ≤ 700)	> 30%	CAS number:	25068-38-6
		EINECS:	500-033-5
		REACH Registration number:	01-2119456619-26
		CLP Classification:	H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H411 Aquatic Chronic 2
		R-Phrases:	R36/38 R43 R51/53

For the full text of the H & R phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: remove contaminated clothing, rinse with plenty of water, if necessary seek medical

attention.

Eye contact: first prolonged rinsing with water (contact lenses to be removed if this is easily done)

then take to physician.

Ingestion: rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: redness, pain

Eye contact: redness, pain, bad looking

Ingestion: diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: sore throat, cough, shortness of breath, headache

4.3 Indication of any immediate medical attention and special treatment needed:

none

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

none

5.3 Advice for fire-fighters:

Extinguishing agents to be

avoided:

none

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up windRemove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

remove by using absorbent material.

6.4 Reference to other sections:

for further information check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

1

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

8.2 Exposure controls:

Inhalation protection:	if necessary, use an air-purifying face mask in case of respiratory hazards.	
Skin protection:	handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range: /
Boiling point/Boiling range: /
pH: /
pH 1% diluted in water: /
Vapour pressure/20°C,: /

Vapour density: not applicable

Relative density, 20°C:

Appearance/20°C:liquidFlash point:100 °C

Flammability (solid, gas): not applicable

Auto-ignition temperature: //
Upper flammability or explosive //

limit, (Vol %):

Lower flammability or explosive

limit, (Vol %):

Explosive properties: not applicable

Oxidising properties: not applicable

Decomposition temperature: /

Solubility in water: not soluble

Partition coefficient: n- not applicable

octanol/water:

Odour: characteristic
Odour threshold: not applicable
Dynamic viscosity, 20°C: 850 mPa.s

Kinematic viscosity, 20°C: /
Evaporation rate (n-BuAc = 1): /

9.2 Other information:

Volatile organic component (VOC): /
Volatile organic component (VOC): /

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

stable under normal conditions.

10.2 Chemical stability:

extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

none

10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

none

10.6 Hazardous decomposition products:

doesn't decompose with normal use

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

About the preparation itself: No data available

General information: See ingredients under section 3

Calculated acute toxicity, LD50 oral

rat

Calculated acute toxicity, LD50

dermal rat:

12 SECTION 12: Ecological information:

12.1 Toxicity:

No data available

12.2 Persistence and degradability:

No data available

12.3 Bioaccumulative potential:

No data available

12.4 Mobility in soil:

Water hazard class, WGK: 3

Solubility in water: not soluble

12.5 Results of PBT and vPvB assessment:

No data available

12.6 Other adverse effects:

No data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

3082

14.2 UN proper shipping name:

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (mixture with Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight \leq 700)), 9, III, (E)

14.3 Transport hazard class(es):

Class(es): 9
Identification number of the 90
hazard:

14.4 Packing group:

Ш


14.5 Environmental hazards:

environmentally hazardous

14.6 Special precautions for user:

Hazard characteristics: Risk to the aquatic environment and the sewerage system.

Additional guidance:



15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK: 3
Volatile organic component (VOC): /
Volatile organic component (VOC): /
Composition by regulation (EC) none
648/2004:

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

Nr.: number

CAS: Chemical Abstracts Service

EINECS: European INventory of Existing Commercial chemical Substances

WGK: Water hazard class

WGK 1: slightly hazardous for water

WGK 2: hazardous for water

WGK3: extremely hazardous for water

ADR: Accord européen relatif au transport international des marchandises Dangereuses

par Route

TLV: Threshold Limit Value

PTB: persistent, toxic, bioaccumulative

vPvB: very persistent and very bioaccumulative substances
CLP: Classification, Labelling and Packaging of chemicals

DPD: Dangerous Preparations Directive

Legend to the R & H Phrases used in the safety data sheet:

R36/38: Irritating to eyes and skin. R43: May cause sensitisation by skin contact. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H315 Skin Irrit. 2: Causes skin irritation. H317 Skin Sens. 1: May cause an allergic skin reaction. H319 Eye Irrit. 2: Causes serious eye irritation. H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Reason of revision, changes of following items:

Sections: 2.1, 2.2

MSDS reference number:

ECM-105969,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 453/2010. Classification has been calculated in accordance with the European directive 67/548/EWG, 1999/45/EC and regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.