

19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- **1.1 Product identifier:**
- 19480-B Rocathaan Hotspray PA 480-ESD Base

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Base for Hotspray

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Prokol Protective Coatings Duizeldonksestraat 44 5705 CA Helmond - Noord-Brabant - Nederland Phone: +31 (0) 85 78 200 20 sds@prokol.nl www.prokol.com

1.4 Emergency telephone number: +31 (0) 85 78 200 20 Mon - Fri 8am - 4.45pm

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Corr. 1C: Skin corrosion, Category 1C, H314 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P264: Wash thoroughly after handling.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-; Diethylmethylbenzenediamine; Glycerylpoly(oxypropeen)triamine **UFI:** 59D0-508N-M00Q-9AFF

2.3 Other hazards:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Formulated polyamines

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification				
CAS: EC:	9046-10-0 618-561-0	Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- Self-classified aminomethylethoxy)- ⁽¹⁾				
	Not relevant :01-2119557899-12- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1C: H314 - Danger	50 - <75 %		
CAS:	68479-98-1	Diethylmethylbenzene	diamine ⁽¹⁾ ATP CLP00			
EC: 270-877-4 Index: 612-130-00-0 REACH:01-2119486805-2 XXXX	612-130-00-0 :01-2119486805-25-	Regulation 1272/2008	Acute Tox. 4: H302+H312; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; STOT RE 2: H373 - Warning	10 - <25 %		
CAS:		Glycerylpoly(oxyprope	een)triamine ⁽¹⁾ Self-classified			
	Not relevant Not relevant Not relevant	Regulation 1272/2008	Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger 🔗	5 - <10 %		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute to	xicity	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- aminomethylethoxy)-	LD50 oral	480 mg/kg	Rat
CAS: 9046-10-0	LD50 dermal	Not relevant	
EC: 618-561-0	LC50 inhalation vapour	Not relevant	
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg	Rat
CAS: 68479-98-1	LD50 dermal	1100 mg/kg	Rat
EC: 270-877-4	LC50 inhalation vapour	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation. Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.-General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.-Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.-Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.-Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C
Maximum time:	12 Months

B.-General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 9046-10-0	Dermal	Not relevant	Not relevant	2.5 mg/kg	Not relevant
EC: 618-561-0	Inhalation	Not relevant	Not relevant	10.58 mg/m ³	Not relevant
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.13 mg/m ³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	0.1 mg/kg	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.1 mg/m ³	Not relevant

PNEC:

Identification				
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	STP	7.5 mg/L	Fresh water	0.015 mg/L
CAS: 9046-10-0	Soil	0.018 mg/kg	Marine water	0.014 mg/L
EC: 618-561-0	Intermittent	0.15 mg/L	Sediment (Fresh water)	0.132 mg/kg
	Oral	0.00693 g/kg	Sediment (Marine water)	0.125 mg/kg
Diethylmethylbenzenediamine	STP	17 mg/L	Fresh water	0.001 mg/L
CAS: 68479-98-1	Soil	0.0056 mg/kg	Marine water	0 mg/L
EC: 270-877-4	Intermittent	0.005 mg/L	Sediment (Fresh water)	0.029 mg/kg
	Oral	0.002 g/kg	Sediment (Marine water)	0.003 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.-Respiratory protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks				
	Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: K)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.				
C	CSpecific protection for the hands								
	Pictogram	PPE	Labelling	CEN Standard	Remarks				
	Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.				
	As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.								
D	Eye and face pr	otection							



19480-B - Rocathaan Hotspray PA 480-ESD - Base

	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory face protection	Fac	e shield	CAT II	UNE-	EN 166:2002 EN ISO 18526-1 al 4:2020 EN ISO 18526-1 al 4:2020 ISO 4007:2018		lean daily and disinfect periodically according to the manufacturer´s nstructions. Use if there is a risk of splashing.
E	-Body protection	۱						
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	protect	le clothing for tion against nical risks		UNE- I 1 EN	034:2005+A1:2009 EN ISO 18526-1 al 4:2020 EN ISO 13982- :2005/A1:2011 ISO 6529:2013 ISO 6530:2005 EN 464:1995	For p	rofessional use only. Clean periodica according to the manufacturer's instructions.
	Mandatory foot protection	protect	footwear for tion against nical risk	CAT III		ISO 20345:2022 I 13832-1:2019	Repl	ace boots at any sign of deterioration
			ANS ISO 3864-1:201	I Z358-1 1, ISO 3864-4	2011	● + ▼		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
	Emergency sh	ower				Eyewash station	าร	
		vironmen [#]	tal protection					nt any spillage of the product
ano Vo Wit	d its container. F blatile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a	For more of compour ective 201): at 20 °C:	nds: 10/75/EU, thi 5.66 66.7		is the f	ollowing charact		
ano Vo Wit	d its container. F blatile organic (th regard to Dire V.O.C. (Supply)	For more of compour ective 201): at 20 °C: n number:	nds: 10/75/EU, thi 5.66 66.7 : 8	s product ha % weight	is the f			
and Vo Wit	d its container. F platile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon	For more of compour ective 201): at 20 °C: n number: ular weigh	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2	s product ha % weight kg/m ³ (66. 29 g/mol	ns the f			
and Vo Wit	d its container. F platile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon Average molect	For more of compour ective 201): at 20 °C: n number: ular weigh	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2 CHEMICAL	s product ha % weight kg/m ³ (66. 29 g/mol PROPERTIE	ns the f 7 g/L) ES	ollowing charact		
and Vo Wit	d its container. F blatile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon Average molecu N 9: PHYSICA	For more of compour ective 201): at 20 °C: n number: ular weigh	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2 CHEMICAL vsical and ch	s product ha % weight kg/m ³ (66. 29 g/mol PROPERTIE	ns the f 7 g/L) ES pertie	ollowing charact		
and Vo Wit	d its container. F blatile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon Average molect N 9: PHYSICA formation on b	For more of compour ective 201): at 20 °C: n number: ular weigh	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2 CHEMICAL vsical and ch	s product ha % weight kg/m ³ (66. 29 g/mol PROPERTIE	ns the f 7 g/L) ES pertie	ollowing charact		
and Vo Wif	d its container. F platile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon Average molecu N 9: PHYSICA formation on b r complete inform	For more of compour ective 201): at 20 °C: a number: ular weigh AL AND (basic phy mation se	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2 CHEMICAL vsical and ch	s product ha % weight kg/m ³ (66. 29 g/mol PROPERTIE	T g/L) 7 g/L) S pertie	ollowing charact		
and Vo With TIO Int For Ap Phy	d its container. F blatile organic of th regard to Dire V.O.C. (Supply) V.O.C. density a Average carbon Average molecu N 9: PHYSICA formation on b r complete inform opearance:	For more of compour ective 201): at 20 °C: a number: ular weigh AL AND (basic phy mation se	nds: 10/75/EU, thi 5.66 66.7 : 8 nt: 236.2 CHEMICAL vsical and ch	s product ha % weight kg/m ³ (66. 29 g/mol PROPERTIE nemical pro t datasheet. Liqu	T g/L) 7 g/L) S pertie	ollowing charact		

Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not relevant *
Volatility:	
Boiling point at atmospheric pressure:	187 °C
Vapour pressure at 20 °C:	141 Pa
*Not relevant due to the nature of the product, not providir	g information property of its hazards.



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SEC	TION 9: PHYSICAL AND CHEMICAL PROPE	ERTIES (continued)
	Vapour pressure at 50 °C:	886.46 Pa (0.89 kPa)
	Evaporation rate at 20 °C:	Not relevant *
	Product description:	
	Density at 20 °C:	1178.5 kg/m³
	Relative density at 20 °C:	1.179
	Dynamic viscosity at 20 °C:	264.55 cP
	Kinematic viscosity at 20 °C:	224.48 mm²/s
	Kinematic viscosity at 40 °C:	Not relevant *
	Concentration:	Not relevant *
	pH:	Not relevant *
	Vapour density at 20 °C:	Not relevant *
	Partition coefficient n-octanol/water 20 °C:	Not relevant *
	Solubility in water at 20 °C:	Not relevant *
	Solubility properties:	Not relevant *
	Decomposition temperature:	Not relevant *
	Melting point/freezing point:	Not relevant *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Not relevant *
	Autoignition temperature:	405 °C
	Lower flammability limit:	Not relevant *
	Upper flammability limit:	Not relevant *
	Particle characteristics:	
	Median equivalent diameter:	Not relevant *
9.2	Other information:	
	Information with regard to physical hazard	classes:
	Explosive properties:	Not relevant *
	Oxidising properties:	Not relevant *
	Corrosive to metals:	Not relevant *
	Heat of combustion:	Not relevant *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Not relevant *
	Surface tension at 20 °C:	Not relevant *
	Refraction index:	Not relevant *
	*Not relevant due to the nature of the product, not provid	ing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 10: STABILITY AND REACTIVITY (continued)

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids Avoid strong acids	Water Not applicable	Oxidising materials Precaution	Combustible materials Not applicable	Others Avoid alkalis or strong
Avoid strong acids	Not applicable	Frecaution	Not applicable	bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3. - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Talc (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3. Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus	
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg	Rat	
CAS: 68479-98-1 EC: 270-877-4	LD50 dermal	1100 mg/kg	Rat	
	LC50 inhalation vapour	>20 mg/L		
Glycerylpoly(oxypropeen)triamine CAS: 64852-22-8 EC: Not relevant	LD50 oral	>2000 mg/kg		
	LD50 dermal	>2000 mg/kg		
	LC50 inhalation gases	>20000 mg/L		
	LC50 inhalation vapour	>20 mg/L		
	LC50 inhalation dust	>5 mg/L		
	LC50 inhalation mist	>5 mg/L		
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- aminomethylethoxy)-	LD50 oral	480 mg/kg	Rat	
CAS: 9046-10-0 EC: 618-561-0	LD50 dermal	2979.7 mg/kg	Rabbit	
	LC50 inhalation gases	>20000 mg/L		
	LC50 inhalation vapour	>20 mg/L		
	LC50 inhalation dust	>5 mg/L		
	LC50 inhalation mist	>5 mg/L		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 9046-10-0	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 618-561-0	EC50	>10 - 100 mg/L (72 h)		Algae
Diethylmethylbenzenediamine	LC50	194 mg/L (48 h)	Leuciscus idus	Fish
CAS: 68479-98-1	EC50	0.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 270-877-4	EC50	Not relevant		
Glycerylpoly(oxypropeen)triamine	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 64852-22-8	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: Not relevant	EC50	>10 - 100 mg/L (72 h)		Algae

12.2 Persistence and degradability:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

Identification	Degradability		Biodegradability	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	BOD5	Not relevant	Concentration	17.6 mg/L
CAS: 9046-10-0	COD	Not relevant	Period	28 days
EC: 618-561-0	BOD5/COD	Not relevant	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	BCF	
CAS: 9046-10-0	Pow Log	1.34
EC: 618-561-0	Potential	

12.4 Mobility in soil:

Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION **

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

** Changes with regards to the previous version



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 14: TRANSPO	RT INFORMATION ** (con	tinued)
14.2	UN number or ID number: UN proper shipping name: Transport hazard class (es):	PAINT RELATED MATERIAL 8
14.4	Labels: • Packing group:	8 III
	Environmental hazards:	Yes
	Special precautions for us	
	Special regulations: Tunnel restriction code:	163, 367 E
	Physico-Chemical properties:	
	Limited quantities:	5 L
14.7	Maritime transport in bulk according to IMO instruments:	Not relevant
Transport of dange	erous goods by sea:	
With regard to IMDG	41-22:	
14.1	UN number or ID number:	UN3066
	UN proper shipping name:	PAINT RELATED MATERIAL
14.3	Transport hazard class (es):	8
· · ·	Labels:	8
	Packing group:	III
	Marine pollutant:	Yes
14.6	Special precautions for use	
	Special regulations:	163, 223, 367
	EmS Codes:	F-A, S-B
	Physico-Chemical properties:	5 L
	Limited quantities: Segregation group:	Not relevant
14 7	Maritime transport in	Not relevant
14.7	bulk according to IMO instruments:	Not relevant
Transport of dange	erous goods by air:	
With regard to IATA/		
	UN number or ID number:	11N3066
	UN proper shipping name:	
	Transport hazard class (es):	8
	Labels:	8
	Packing group:	III
	Environmental hazards:	Yes
14.6	Special precautions for us	er
	Physico-Chemical properties:	see section 9
14.7	Maritime transport in bulk according to IMO instruments:	Not relevant

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 15: REGULATORY INFORMATION (continued)

- : Not relevant
- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant

- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains Di- 'isononyl' phthalate. 1. Shall not be used as substances or in mixtures, in concentrations greater than 0,1 % by weight of the plasticised material, in toys and childcare articles which can be placed in the mouth by children. 2. Such toys and childcare articles containing these phthalates in a concentration greater than 0,1 % by weight of the plasticised material shall not be placed on the market. 4. For the purpose of this entry 'childcare article' shall mean any product intended to facilitate sleep, relaxation, hygiene, the feeding of children or sucking on the part of children.

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. **Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplacespecific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: TRANSPORT INFORMATION (SECTION 14):

· UN number

Texts of the legislative phrases mentioned in section 2:

H318: Causes serious eye damage.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

- H302: Harmful if swallowed.
- H314: Causes severe skin burns and eye damage.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



19480-B - Rocathaan Hotspray PA 480-ESD - Base

SECTION 16: OTHER INFORMATION (continued) Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. **Classification procedure:** Eye Dam. 1: Calculation method STOT RE 2: Calculation method Aquatic Chronic 2: Calculation method Acute Tox. 4: Calculation method Skin Corr. 1C: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.