

**SECTION 1: Identification of the substance/mixture and of the company/undertaking:****1.1 Product identifier:****Rocathaan Hotspray MP 620-SP base**

UFI: /

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

/

Concentration in use: /

**1.3 Details of the supplier of the safety data sheet:****PROKOL**

Duizeldonksestraat 44

NL5705CA HELMOND (NEDERLAND)

Phone: 0031492547665 – E-mail: [jw.koolen@prokol.nl](mailto:jw.koolen@prokol.nl) – Website: <http://www.prokol.nl/>**1.4 Emergency telephone number:**

+31 88 755 8000 Nationaal Vergiftigingen Informatie Centrum (NVIC) (Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.)

**SECTION 2: Hazards identification:****2.1 Classification of the substance or mixture:**

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008

**EUH211 H315 Skin Irrit. 2 H317 Skin Sens. 1B H319 Eye Irrit. 2 H360FD Repr. 1B H373 STOT RE 2  
H411 Aquatic Chronic 2 EUH208****2.2 Label elements:**

Pictograms



## Signal word

Danger

## Hazard statements

<b>EUH211:</b>	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>H315 Skin Irrit. 2:</b>	Causes skin irritation.
<b>H317 Skin Sens. 1B:</b>	May cause an allergic skin reaction.
<b>H319 Eye Irrit. 2:</b>	Causes serious eye irritation.
<b>H360FD Repr. 1B:</b>	May damage fertility. May damage the unborn child.
<b>H373 STOT RE 2:</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H411 Aquatic Chronic 2:</b>	Toxic to aquatic life with long lasting effects.
<b>EUH208:</b>	Contains ( dibutyltin dilaurate ). May produce an allergic reaction.

## Precautionary statements

<b>P280:</b>	Wear protective gloves, protective clothing, eye protection, face protection.
<b>P302+P352:</b>	IF ON SKIN: Wash with plenty of soap and water.
<b>P305+P351+P338:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P308+P313:</b>	IF exposed or concerned: Get medical advice/attention.
<b>P362+P364:</b>	Take off contaminated clothing and wash it before reuse.
<b>P501:</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

## Contains

3-aminopropyltriethoxysilane 2,4-diamino-3,5-diethyltoluene

## 2.3 Other hazards:

None

## SECTION 3: Composition/information on ingredients:

2,4-diamino-3,5-diethyltoluene	≤ 20 %	CAS number: 68479-98-1 EINECS: 270-877-4 REACH Registration number: 01-2119486805-25 CLP Classification: <b>H302 Acute tox. 4</b> <b>H312 Acute tox. 4</b> <b>H319 Eye Irrit. 2</b> <b>H373 STOT RE 2</b> <b>H400 Aquatic Acute 1</b> <b>H410 Aquatic Chronic 1</b>
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	≤ 10 %	CAS number: 904-153-2 EINECS: / REACH Registration number: 01-2119488034-38 CLP Classification: <b>H319 Eye Irrit. 2</b>
tris(2-chloro-1-methylethyl) phosphate	≤ 7 %	CAS number: 13674-84-5 EINECS: 237-158-7 REACH Registration number: 01-2119447716-31 CLP Classification: <b>H302 Acute tox. 4</b>

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	≤ 3 %	CAS number: 102-60-3 EINECS: 203-041-4 REACH Registration number: 01-2119552434-41 CLP Classification: <b>H319 Eye Irrit. 2</b>
Titanium dioxide	≤ 2 %	CAS number: 13463-67-7 EINECS: 236-675-5 REACH Registration number: 01-2119489379-17 CLP Classification: <b>H351i Carc. 2</b>
3-aminopropyltriethoxysilane	≤ 2 %	CAS number: 919-30-2 EINECS: 213-048-4 REACH Registration number: 01-2119480479-24 CLP Classification: <b>H302 Acute tox. 4 H314 Skin Corr. 1B H318 Eye Dam. 1 H317 Skin Sens. 1B</b>
dibutyltin dilaurate	≤ 0.6 %	CAS number: 77-58-7 EINECS: 201-039-8 REACH Registration number: 01-2119496068-27 CLP Classification: <b>H314 Skin Corr. 1C H318 Eye Dam. 1 H317 Skin Sens. 1 H341 Muta. 2 H360FD Repr. 1B H370 STOT SE 1 H372 STOT RE 1 H400 Aquatic Acute 1 H410 Aquatic Chronic 1</b>
(2-hydroxypropyl) trimethylammonium 2-ethylhexanoate	≤ 0.2 %	CAS number: 62314-22-1 EINECS: 263-502-0 REACH Registration number: 01-2120767468-38 CLP Classification: <b>H314 Skin Corr. 1C H318 Eye Dam. 1 H361fd Repr. 2</b>

For the full text of the H phrases mentioned in this section, see section 16.

## SECTION 4: First aid measures:

### 4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

<b>Skin contact:</b>	Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.
<b>Eye contact:</b>	Thoroughly rinse with water (contact lenses to be removed if this is easily done) then take to physician.
<b>Ingestion:</b>	Rinse mouth, do not induce vomiting, take to hospital immediately.
<b>Inhalation:</b>	Let sit upright, fresh air, rest and take to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed:

<b>Skin contact:</b>	Redness, pain
<b>Eye contact:</b>	Redness, pain, blurred vision
<b>Ingestion:</b>	Diarrhoea, headache, abdominal cramps, sleepiness, vomiting
<b>Inhalation:</b>	Sore throat, cough, shortness of breath, headache

### 4.3 Indication of any immediate medical attention and special treatment needed:

None

## SECTION 5: Fire-fighting measures:

### 5.1 Extinguishing media:

CO2, foam, powder, sprayed water

### 5.2 Special hazards arising from the substance or mixture:

None

### 5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

## SECTION 6: Accidental release measures:

### 6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

### 6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

### 6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

### 6.4 Reference to other sections:

For further information, check sections 8 & 13.

## SECTION 7: Handling and storage:

### 7.1 Precautions for safe handling:

Handle with care to avoid spillage.

### 7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

### 7.3 Specific end use(s):

/





## SECTION 8: Exposure controls/personal protection:

### 8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the workplace exposure limit values are known

/

## 8.2 Exposure controls:

<b>Inhalation protection:</b>	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
<b>Skin protection:</b>	Handling with Viton-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
<b>Eye protection:</b>	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
<b>Other protection:</b>	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	
<b>Environmental controls:</b>	Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions. For further information, check sections 6 and 13.	
<b>Engineering controls:</b>	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. For further information, check section 7.	

## SECTION 9: Physical and chemical properties:

### 9.1 Information on basic physical and chemical properties:

<b>Appearance/20°C:</b>	Liquid
<b>Colour:</b>	grey
<b>Odour:</b>	characteristic
<b>Melting point/melting range:</b>	/
<b>Boiling point/Boiling range:</b>	100 °C – 308 °C
<b>Flammability (solid, gas):</b>	Not applicable
<b>Lower flammability or explosive limit, (Vol %):</b>	/
<b>Upper flammability or explosive limit, (Vol %):</b>	/
<b>Flash point:</b>	/
<b>Auto-ignition temperature:</b>	/
<b>Decomposition temperature:</b>	/
<b>pH:</b>	/
<b>pH 1% diluted in water:</b>	/
<b>Kinematic viscosity, 40°C:</b>	1 mm <sup>2</sup> /s
<b>Solubility in water:</b>	Not soluble
<b>Partition coefficient: n-octanol/water:</b>	Not applicable
<b>Vapour pressure/20°C,:</b>	11 Pa
<b>Relative density, 20°C:</b>	1.0200 kg/l
<b>Vapour density:</b>	Not applicable
<b>Particle characteristics:</b>	/

### 9.2 Other information:

<b>Dynamic viscosity, 20°C:</b>	1 mPa.s
<b>Sustained combustion test:</b>	/
<b>Evaporation rate (n-BuAc = 1):</b>	2,500.000
<b>Volatile organic component (VOC):</b>	2.85 %
<b>Volatile organic component (VOC):</b>	29.529 g/l

## SECTION 10: Stability and reactivity:

### 10.1 Reactivity:

Stable under normal conditions.

### 10.2 Chemical stability:

Extremely high or low temperatures.

### 10.3 Possibility of hazardous reactions:

None

### 10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

### 10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

### 10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

## SECTION 11: Toxicological information:

### 11.1 Information on toxicological effects:

#### a) acute toxicity:

Not classified according to the CLP calculation method

**Calculated acute toxicity, ATE oral:** > 2,000 mg/kg

**Calculated acute toxicity, ATE dermal:** > 2,000 mg/kg

2,4-diamino-3,5-diethyltoluene	LD50 oral, rat:	738 mg/kg
	LD50 dermal, rabbit:	1,100 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	LD50 oral, rat:	≥ 5,000 mg/kg
	LD50 dermal, rabbit:	≥ 5,000 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l
tris(2-chloro-1-methylethyl) phosphate	LD50 oral, rat:	500 mg/kg
	LD50 dermal, rabbit:	≥ 5,000 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	LD50 oral, rat: ≥ 5,000 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: 10 mg/l
Titanium dioxide	LD50 oral, rat: ≥ 5,000 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
3-aminopropyltriethoxysilane	LD50 oral, rat: 500 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
dibutyltin dilaurate	LD50 oral, rat: 500 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
(2-hydroxypropyl) trimethylammonium 2-ethylhexanoate	LD50 oral, rat: ≥ 5,000 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l

b) skin corrosion/irritation:

**H315 Skin Irrit. 2:** Causes skin irritation.

c) serious eye damage/irritation:

**H319 Eye Irrit. 2:** Causes serious eye irritation.

d) respiratory or skin sensitisation:

**H317 Skin Sens. 1B:** May cause an allergic skin reaction.

e) germ cell mutagenicity:

Not classified according to the CLP calculation method

f) carcinogenicity:

Not classified according to the CLP calculation method

g) reproductive toxicity:

**H360FD Repr. 1B:** May damage fertility. May damage the unborn child.

h) STOT-single exposure:

Not classified according to the CLP calculation method

i) STOT-repeated exposure:

**H373 STOT RE 2:** May cause damage to organs through prolonged or repeated exposure.

i) aspiration hazard:

Not classified according to the CLP calculation method

## 11.2 Information on other hazards:

No additional data available

## SECTION 12: Ecological information:

### 12.1 Toxicity:

2,4-diamino-3,5-diethyltoluene	LC50 (Fish): 200 mg/L (48h) EC50 (Daphnia): 0,5 mg/L (48h) EC50 (soil microorganisms): > 170 mg/L (24h)
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl -1,-dioxane-5-methanol	LC50 (Fish): 1250 mg/L NOEC (Fish): 500 mg/L
tris(2-chloro-1-methylethyl) phosphate	LC50 (Fish): 98 mg/L (96h) NOEC (Fish): 9.8 mg/L (96h) EC50 (Daphnia): 131 mg/L (48h) NOEC (Daphnia): 33.5 mg/L (48h) EC50 (Algae): 82 mg/L (72h) NOEC (Algae): 13 mg/L (72h) EC50 (soil microorganisms): 784 mg/L (3h)

### 12.2 Persistence and degradability:

No additional data available

### 12.3 Bioaccumulative potential:

No additional data available

### 12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 2  
Solubility in water: Not soluble

### 12.5 Results of PBT and vPvB assessment:

No additional data available

### 12.6 Endocrine disrupting properties:

No additional data available

### 12.7 Other adverse effects:

No additional data available

## SECTION 13: Disposal considerations:

### 13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

## SECTION 14: Transport information:





#### 14.1 UN number:

3082

#### 14.2 UN proper shipping name:

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (mixture with 2,4-diamino-3,5-diethyltoluene; dibutyltin dilaurate), 9, III, (-)

#### 14.3 Transport hazard class(es):

Class(es):	9
Identification number of the hazard:	90

#### 14.4 Packing group:

III

#### 14.5 Environmental hazards:

Environmentally hazardous

#### 14.6 Special precautions for user:

Hazard characteristics:	Risk to the aquatic environment and the sewerage system.
Additional guidance:	Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments:

Not applicable

### SECTION 15: Regulatory information:

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV):	2
Volatile organic component (VOC):	2.850 %
Volatile organic component (VOC):	29.529 g/l
Composition by regulation (EC) 648/2004:	Phosphates 5% - 15%, Zeolites < 5%

#### 15.2 Chemical Safety Assessment:

No data available

### SECTION 16: Other information:

#### Legend to abbreviations used in the safety data sheet:

<b>ADR:</b>	The European Agreement concerning the International Carriage of Dangerous Goods by Road
<b>ATE:</b>	Acute Toxicity Estimate
<b>BCF:</b>	Bioconcentration factor
<b>CAS:</b>	Chemical Abstracts Service
<b>CLP:</b>	Classification, Labelling and Packaging of chemicals
<b>EINECS:</b>	European INventory of Existing commercial Chemical Substances
<b>LC50:</b>	median Lethal Concentration for 50% of subjects
<b>LD50:</b>	median Lethal Dose for 50% of subjects
<b>Nr.:</b>	Number
<b>PTB:</b>	Persistent, Toxic, Bioaccumulative
<b>STOT:</b>	Specific Target Organ Toxicity
<b>UFI:</b>	Unique Formula Identifier
<b>vPvB:</b>	very Persistent and very Bioaccumulative substances
<b>WGK:</b>	Water hazard class
<b>WGK 1:</b>	Slightly hazardous for water
<b>WGK 2:</b>	Hazardous for water
<b>WGK 3:</b>	Extremely hazardous for water

#### Legend to the H Phrases used in the safety data sheet

**EUH208:** Contains ( dibutyltin dilaurate ). May produce an allergic reaction. **EUH211:** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **H302 Acute tox. 4:** Harmful if swallowed. **H312 Acute tox. 4:** Harmful in contact with skin. **H314 Skin Corr. 1B H318 Eye Dam. 1:** Causes severe skin burns and eye damage. **H314 Skin Corr. 1C H318 Eye Dam. 1:** Causes severe skin burns and eye damage. **H315 Skin Irrit. 2:** Causes skin irritation. **H317 Skin Sens. 1:** May cause an allergic skin reaction. **H317 Skin Sens. 1B:** May cause an allergic skin reaction. **H319 Eye Irrit. 2:** Causes serious eye irritation. **H341 Muta. 2:** Suspected of causing genetic defects. **H351i Carc. 2:** Suspected of causing cancer. **H360FD Repr. 1B:** May damage fertility. May damage the unborn child. **H361fd Repr. 2:** Suspected of damaging fertility. Suspected of damaging the unborn child. **H370 STOT SE 1:** Causes damage to organs. **H372 STOT RE 1:** Causes damage to organs through prolonged or repeated exposure. **H373 STOT RE 2:** May cause damage to organs through prolonged or repeated exposure. **H400 Aquatic Acute 1:** Very toxic to aquatic life. **H410 Aquatic Chronic 1:** Very toxic to aquatic life with long lasting effects. **H411 Aquatic Chronic 2:** Toxic to aquatic life with long lasting effects.

#### CLP Calculation method

Calculation method

#### Reason of revision, changes of following items

Sections: 2.1, 2.2, 3, 9.2, 15.1, 16

#### SDS reference number

ECM-112778,00

*This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2020/878. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.*