

## 19870-B - Rocathaan Hotspray PA 870-WR - Base

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- **1.1 Product identifier:**
- 19870-B Rocathaan Hotspray PA 870-WR Base

## Other means of identification:

Not relevant

## **1.2** Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Base for Hotspray

Uses advised against: All uses not specified in this section or in section 7.3

#### **1.3** Details of the supplier of the safety data sheet:

Prokol Protective Coatings Duizeldonksestraat 44 5705 CA Helmond - Noord-Brabant - Nederland Phone: +31 (0) 85 78 200 20 sds@prokol.nl www.prokol.com

1.4 Emergency telephone number: +31 (0) 85 78 200 20 Mon - Fri 8am - 4.45pm

## SECTION 2: HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture:

## CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Corr. 1C: Skin corrosion, Category 1C, H314 Skin Sens. 1: Sensitisation, skin, Category 1, H317 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373

## 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

Danger



## Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements:
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352: IF ON SKIN: Wash with plenty of water.
P302+P352: IF ON SKIN: Wash with plenty of for each off and the plant of the plant of the plant.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

## Supplementary information:

Contains 3-aminopropyltriethoxysilane.

## Substances that contribute to the classification



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

## SECTION 2: HAZARDS IDENTIFICATION (continued)

Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-; Diethylmethylbenzenediamine; 4,4 ´-methylenebis[N-sec-butylaniline]; Glycerylpoly(oxypropeen)triamine **UFI:** DUE0-80PT-400M-6FXM

#### 2.3 Other hazards:

Product does not meet PBT/vPvB criteria Endocrine-disrupting properties: The product does not meet the criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Not relevant

#### 3.2 Mixture:

#### Chemical description: Formulated polyamines

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification			
CAS: EC:	9046-10-0 618-561-0	Poly[oxy(methyl-1 aminomethylethoxy)-	,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- Self-classified			
	Not relevant :01-2119557899-12- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr.	50 - <75 %		
CAS:	68479-98-1	Diethylmethylbenzene	diamine <sup>(1)</sup> ATP CLP00			
	270-877-4 612-130-00-0 :01-2119486805-25- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H312; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; STOT RE 2: H373 - Warning	10 - <25 %		
CAS:	5285-60-9	4,4'-methylenebis[N-sec-butylaniline] <sup>(1)</sup> Self-classified				
	226-122-6 Not relevant :Not relevant	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317; STOT RE 2: H373 - Warning	5 - <10 %		
CAS:	64852-22-8	Glycerylpoly(oxyprop	een)triamine <sup>(1)</sup> Self-classified			
	Not relevant Not relevant :Not relevant	Regulation 1272/2008	Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	2.5 - <5 %		
CAS:	919-30-2	3-aminopropyltrietho	xysilane <sup>(1)</sup> Self-classified			
	213-048-4 612-108-00-0 :01-2119480479-24- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: 🔗 🔶 H317 - Danger	<1 %		

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

## To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute to	oxicity	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- aminomethylethoxy)-	LD50 oral	480 mg/kg	Rat
CAS: 9046-10-0	LD50 dermal	Not relevant	
EC: 618-561-0	LC50 inhalation vapour	Not relevant	
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg	Rat
CAS: 68479-98-1	LD50 dermal	1100 mg/kg	Rat
EC: 270-877-4	LC50 inhalation vapour	Not relevant	
4,4 '-methylenebis[N-sec-butylaniline]	LD50 oral	500 mg/kg	
CAS: 5285-60-9	LD50 dermal	Not relevant	
EC: 226-122-6	LC50 inhalation vapour	Not relevant	
3-aminopropyltriethoxysilane	LD50 oral	1491 mg/kg	Rat
CAS: 919-30-2	LD50 dermal	Not relevant	
EC: 213-048-4	LC50 inhalation vapour	Not relevant	



## SECTION 4: FIRST AID MEASURES

## 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

## By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

## SECTION 5: FIREFIGHTING MEASURES

## 5.1 Extinguishing media:

## Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

#### Unsuitable extinguishing media:

Non-applicable

## 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures: For non-emergency personnel:



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

## SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

## For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

## 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.-General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.-Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.-Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.-Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.-Specific storage requirements

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C

Maximum time: 12 Months

B.-General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

#### DNEL (Workers):

		Short e	Short exposure		xposure
Identification		Systemic	Local	Systemic	Local
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 9046-10-0	Dermal	Not relevant	Not relevant	2.5 mg/kg	Not relevant
EC: 618-561-0	Inhalation	Not relevant	Not relevant	10.58 mg/m <sup>3</sup>	Not relevant
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.13 mg/m <sup>3</sup>	Not relevant
3-aminopropyltriethoxysilane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 919-30-2	Dermal	Not relevant	Not relevant	2 mg/kg	Not relevant
EC: 213-048-4	Inhalation	Not relevant	Not relevant	14 mg/m <sup>3</sup>	Not relevant

## DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	0.1 mg/kg	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.1 mg/m <sup>3</sup>	Not relevant
3-aminopropyltriethoxysilane	Oral	Not relevant	Not relevant	1 mg/kg	Not relevant
CAS: 919-30-2	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 213-048-4	Inhalation	Not relevant	Not relevant	3.5 mg/m <sup>3</sup>	Not relevant

## PNEC:

Identification				
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	STP	7.5 mg/L	Fresh water	0.015 mg/L
CAS: 9046-10-0	Soil	0.018 mg/kg	Marine water	0.014 mg/L
EC: 618-561-0	Intermittent	0.15 mg/L	Sediment (Fresh water)	0.132 mg/kg
	Oral	0.00693 g/kg	Sediment (Marine water)	0.125 mg/kg
Diethylmethylbenzenediamine	STP	17 mg/L	Fresh water	0.001 mg/L
CAS: 68479-98-1	Soil	0.0056 mg/kg	Marine water	0 mg/L
EC: 270-877-4	Intermittent	0.005 mg/L	Sediment (Fresh water)	0.029 mg/kg
	Oral	0.002 g/kg	Sediment (Marine water)	0.003 mg/kg
3-aminopropyltriethoxysilane	STP	1.3 mg/L	Fresh water	Not relevant
CAS: 919-30-2	Soil	Not relevant	Marine water	Not relevant
EC: 213-048-4	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant

## 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.-Respiratory protection



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: K)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
C	Specific protect	ion for the hands			
	Pictogram	PPE	Labelling	CEN Standard	Remarks

Pictogram	PPE	Labelling	CEN Standard	Remarks	
Mandatory hand	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.	

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.-Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield		EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 UNE-EN ISO 18526-1 al 4:2020 EN ISO 13982- 1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Evewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

## **Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

## Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	0 kg/m³ (0 g/L)
Average carbon number:	Not relevant
Average molecular weight:	Not relevant



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

SEC	TION 9: PHYSICAL AND CHEMICAL PROP	PERTIES
9.1	Information on basic physical and chemic	cal properties:
	For complete information see the product data	asheet.
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Characteristic
	Colour:	According to the markings on the package
	Odour:	Characteristic
	Odour threshold:	Not relevant *
	Volatility:	
	Boiling point at atmospheric pressure:	227 °C
	Vapour pressure at 20 °C:	2 Pa
	Vapour pressure at 50 °C:	37.1 Pa (0.04 kPa)
	Evaporation rate at 20 °C:	Not relevant *
	Product description:	
	Density at 20 °C:	1257 kg/m³
	Relative density at 20 °C:	1.257
	Dynamic viscosity at 20 °C:	Not relevant *
	Kinematic viscosity at 20 °C:	Not relevant *
	Kinematic viscosity at 40 °C:	Not relevant *
	Concentration:	Not relevant *
	pH:	Not relevant *
	Vapour density at 20 °C:	Not relevant *
	Partition coefficient n-octanol/water 20 °C:	Not relevant *
	Solubility in water at 20 °C:	Not relevant *
	Solubility properties:	Not relevant *
	Decomposition temperature:	Not relevant *
	Melting point/freezing point:	Not relevant *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Not relevant *
	Autoignition temperature:	300 °C
	Lower flammability limit:	Not relevant *
	Upper flammability limit:	Not relevant *
	Particle characteristics:	
	Median equivalent diameter:	Not relevant *
9.2	Other information:	
	Information with regard to physical haza	rd classes:
	Explosive properties:	Not relevant *
	Oxidising properties:	Not relevant *
	Corrosive to metals:	Not relevant *
	Heat of combustion:	Not relevant *
	Aerosols-total percentage (by mass) of flammable components: <b>Other safety characteristics:</b>	Not relevant *
	Surface tension at 20 °C:	Not relevant *
	*Not relevant due to the nature of the product, not prov	



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index:

Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

## 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

## 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

## 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

## 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

#### **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide ( $CO_2$ ), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

## Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.

- Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Poly(tetrafluoroethylene) (3); Titanium dioxide (2B); Talc (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### **Other information:**

Not relevant

## Specific toxicology information on the substances:

Identification	Acute to	oxicity	Genus
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg	Rat
CAS: 68479-98-1	LD50 dermal	1100 mg/kg	Rat
EC: 270-877-4	LC50 inhalation vapour	>20 mg/L	
4,4 '-methylenebis[N-sec-butylaniline]	LD50 oral	500 mg/kg	
CAS: 5285-60-9	LD50 dermal	>2000 mg/kg	
EC: 226-122-6	LC50 inhalation dust	>5 mg/L	
Glycerylpoly(oxypropeen)triamine	LD50 oral	>2000 mg/kg	
CAS: 64852-22-8 EC: Not relevant	LD50 dermal	>2000 mg/kg	
	LC50 inhalation gases	>20000 mg/L	
	LC50 inhalation vapour	>20 mg/L	
	LC50 inhalation dust	>5 mg/L	
	LC50 inhalation mist	>5 mg/L	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2- aminomethylethoxy)-	LD50 oral	480 mg/kg	Rat
CAS: 9046-10-0	LD50 dermal	2979.7 mg/kg	Rabbit
EC: 618-561-0	LC50 inhalation gases	>20000 mg/L	
	LC50 inhalation vapour	>20 mg/L	
	LC50 inhalation dust	>5 mg/L	
	LC50 inhalation mist	>5 mg/L	
3-aminopropyltriethoxysilane	LD50 oral	1491 mg/kg	Rat
CAS: 919-30-2	LD50 dermal	4000 mg/kg	Rabbit
EC: 213-048-4	LC50 inhalation vapour	>20 mg/L	

## 11.2 Information on other hazards:

## **Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

## Other information



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Not relevant

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

#### 12.1 Toxicity:

#### Acute toxicity:

Identification		Concentration	Species	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 9046-10-0	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 618-561-0	EC50	>10 - 100 mg/L (72 h)		Algae
Diethylmethylbenzenediamine	LC50	194 mg/L (48 h)	Leuciscus idus	Fish
CAS: 68479-98-1	EC50	0.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 270-877-4	EC50	Not relevant		
4,4 '-methylenebis[N-sec-butylaniline]	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 5285-60-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 226-122-6	EC50	>0.1 - 1 mg/L (72 h)		Algae
Glycerylpoly(oxypropeen)triamine	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 64852-22-8	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: Not relevant	EC50	>10 - 100 mg/L (72 h)		Algae

## 12.2 Persistence and degradability:

## Substance-specific information:

Identification	Degra	adability	Biodegradability	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2- aminomethylethyl)-w-(2-aminomethylethoxy)-	BOD5	Not relevant	Concentration	17.6 mg/L
CAS: 9046-10-0	COD	Not relevant	Period	28 days
EC: 618-561-0	BOD5/COD	Not relevant	% Biodegradable	0 %
3-aminopropyltriethoxysilane	BOD5	Not relevant	Concentration	Not relevant
CAS: 919-30-2	COD	Not relevant	Period	28 days
EC: 213-048-4	BOD5/COD	Not relevant	% Biodegradable	67 %

## 12.3 Bioaccumulative potential:

#### Substance-specific information:

Identification	Bioaccumulation potential	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	BCF	
CAS: 9046-10-0	Pow Log	1.34
EC: 618-561-0	Potential	

# 12.4 Mobility in soil:

Not relevant

# 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

## 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

## 12.7 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

## **13.1 Waste treatment methods:**



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

## SECTION 13: DISPOSAL CONSIDERATIONS (continued)

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous
Code	Description	Waste class (Regulation (EU) No 1357/2014)

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP8 Corrosive

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

## **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION \*\*

	erous goods by land:	
-	2023 and RID 2023:	
14.	1 UN number or ID number:	UN3066
14.	2 UN proper shipping name:	PAINT RELATED MATERIAL
- <b>14</b> .	3 Transport hazard class	8
	(es):	
	Labels:	8
	4 Packing group:	III
14.	5 Environmental hazards:	Yes
14.	6 Special precautions for use	er
	Special regulations:	163, 367
	Tunnel restriction code:	E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.	7 Maritime transport in bulk according to IMO instruments:	Not relevant
Transport of dang	erous goods by sea:	
With regard to IMD		
14.	1 UN number or ID number:	UN3066
á <u>14</u> .	2 UN proper shipping name:	PAINT RELATED MATERIAL
	3 Transport hazard class (es):	8
	Labels:	8
14	4 Packing group:	III
	5 Marine pollutant:	Yes
	6 Special precautions for us	
14.	Special regulations:	163, 223, 367
	EmS Codes:	F-A, S-B
	Physico-Chemical properties:	
	Limited quantities:	5 L
	Segregation group:	Not relevant
14.	7 Maritime transport in bulk according to IMO instruments:	Not relevant

\*\* Changes with regards to the previous version



## 19870-B - Rocathaan Hotspray PA 870-WR - Base

With regard to IATA	A/ICAO 2024:	
/ 14.	1 UN number or ID number	: UN3066
<b>▲ ● &lt; <u>↓</u> &gt;</b> 14.	2 UN proper shipping name	PAINT RELATED MATERIAL
🔍 🗸 14.	3 Transport hazard class	8
	(es):	2
	Labels:	8
	4 Packing group: 5 Environmental hazards:	III Yes
	6 Special precautions for us	
14.		
	Physico-Chemical properties	: see section 9
14.	7 Maritime transport in bulk according to IMO instruments:	Not relevant
es with regards to th	ne previous version	/legislation specific for the substance or mixture

- Regulation (EU) 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant

- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

E2	ENVIRONMENTAL HAZARDS	200	500
Section	Description	Lower-tier	Upper-tier requirements

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects. **Specific provisions in terms of protecting people or the environment:** 

It is recommended to use the information included in this safety data sheet as a basis for conducting workplacespecific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

## 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

## Legislation related to safety data sheets:



## SECTION 16: OTHER INFORMATION (continued) This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878) Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: TRANSPORT INFORMATION (SECTION 14): UN number Texts of the legislative phrases mentioned in section 2: H318: Causes serious eye damage. H373: May cause damage to organs through prolonged or repeated exposure. H411: Toxic to aquatic life with long lasting effects. H317: May cause an allergic skin reaction. H302: Harmful if swallowed. H314: Causes severe skin burns and eye damage. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. **Classification procedure:** Eye Dam. 1: Calculation method STOT RE 2: Calculation method Aquatic Chronic 2: Calculation method Skin Sens. 1: Calculation method Acute Tox. 4: Calculation method Skin Corr. 1C: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -